


DATA SHEET

DVN 630 D4 F4 30 | 142192



- 200 °C constant operation and 400 °C / 2h
- Motor outside of air stream
- Speed controllable
- Drain tray
- Certified according to EN 12101-3:2015 with Certificate 1404-CPR-3027

— ErP compliant range

Operating Point		1	2	3	4	5
Current I	A	5,2	6,1	7,9	7,7	7,6
Power consumption P ₁	W	1302	2420	3959	3836	3744
RPM n	1/min	1483	1470	1457	1458	1460
SPL inlet L _{WA5}	dB(A)	90	90	91	94	95
SPL outlet L _{WA6}	dB(A)	90	89	91	95	97
SPL casing break out L _{WA2}	dB(A)	-	-	-	-	-

Sound power (L _W) dB(A)		Medium Frequency Band								
		Σ	63	125	250	500	1k	2k	4k	8k
Inlet	L _{WA5}	92	65	82	86	86	86	83	79	77
Outlet	L _{WA6}	93	65	85	87	88	86	83	78	71
Casing	L _{WA2}	-	-	-	-	-	-	-	-	-

DVN 630 D4 F4 30 142192	
Voltage U _N	400 V 3~
Current I _{max}	8,5 A
Ambient temperature t _A	50 °C
Medium temperatures t _M	200 °C
Speed Control	f
Motor Protection	
Isolation Class	F
Weight	137,0 kg

